



MONUMENT BOX CASTING SHALL BE E.J.I.W. #2960 WITH SPECIAL ORDER LID

ANNULAR SPACE BETWEEN CASTING AND PAVEMENT SHALL BE FILLED WITH NON-SHRINK GROUT PER O.D.O.T. 705.20

FOR MONUMENT BOXES NOT ON PAVEMENT USE NEENAH 1978A OR E.J.I.W. 8365 CASTING OR EQUAL WITH 1" DIA. x 36" LONG IRON PIN

1" DIA. x 36" LONG IRON PIN TO BE SET BY REG. SURVEYOR WITH CAP

INSTALLATION:

1. CORE BOTH OPENINGS IN PAVEMENT
2. REMOVE DEBRIS AND PREPARE CONC. FOR GROUT PER MANUFACTURERS INSTRUCTIONS
3. COAT PAVEMENT OPENING AND EXTERIOR OF CASTING WITH GROUT
4. INSTALL CASTING AND FINISH FLUSH WITH EXISTING PAVEMENT

<p>CITY OF SOLON ENGINEERING DEPARTMENT</p>	<p>STANDARD DETAIL</p>	<p>CORED/BOXLESS MONUMENT IN RIGID OR FLEXIBLE PAVEMENT</p>
		<p>P-10</p>